

PRODUCT SPECIFICATION

riduce model. No nen e your	Product model:	NS-HLPL-96	NS-HLPL-96NL
-----------------------------	----------------	------------	--------------

DESCRIPTION : LED 595×595 panel light (SMD2835)



Features

Voltage

- 1. Built-in constant current dri ver, high efficiency, stability
- 2. Using the imported SMD as light source, high light efficiency, long lifespan.
- 3. Quick response time, the LED response time is nanosecond.
- 4. Environmental protection, no heavy metals and harmful gas.
- 5. Energy-saving, can save energy more 80% than traditional fluorescent lights.


96W

AC110-240 V


- 7. Start quickly, soft light, protect your eyes.
- 8. Easy to install and use.


Technical Parameter	
Model	96W
LED model	2835
LED Qty	192PCS
Power	96W

Working Frequency Power Efficiency	50/60HZ ≥86%
Luminous Flux	7680LM
Luminous efficiency	80LM/W±10%
Power Factor	≥ 0.9
Colour	WH: 6500K(6020-7040)
Temperature	NW: 4000K (3710-4260)
CRI	Ra ≥ 80
Bean Angle	110º
Working Temperature	-20 to + 5 0 °C
Service life	30,000hr life 5yr warranty





NS-HLPL-96







• Optical characteristic curve











- Instruction of wiring
- 1. Diagram of power supply wiring:



● Installation Instructions (安装示意图)



- 1. Slowly remove the ceiling at an angle;
- 2. Connec driver with lamp;
- 3. Put the lamp on ceiling;
- 4. Pull the lamp down to ensure proper installation;


• Product Package Packed in color box, 8 PCS/ Master carton

• Product Photos



• Packing size :

Model	L (mm)	W (mm)	H (mm)
NS-HLPL-96	625	60	630
NS-HLPL-96NL	625	60	630




01.02.13.071.5116 内盒-625x60x630mm-250g灰底白+A2(100g芯) E坑-四色-覆光膜-6500K格栅灯-A49(2PCS装)

01.02.13.071.5189

内盒-625x60x630mm-250g灰底白+A2 (100g芯) E坑-四色-覆光膜-4000K格栅灯-A49 (2PCS装)




01.02.13.041.3587 外箱-640x255x645mm-250g灰底白+535A(双120g芯) EB坑-四色-覆光膜--6500K格栅灯-A49 (8PCS装)



01.02.13.041.3626

外箱-640x255x645mm-250g灰底白+535A(双120g芯) EB坑-四色-覆光膜--4000K格栅灯-A49 (8PCS装)



Attentions

1.Make sure the power is off before maintenance.

2.Clean the diffuser plates of diffuser of lamp regularly to maintain good light transmittance.

3.Clean the dust of the shell to maintain good heat dissipation performance.

4.Be careful not to use water or corrosive solution for cleaning, it is better to use a dry cloth.

•Warranty and After-sales Service

The period of guarantee is 5 years. Quality assurance is based on the correct storage, installation, use and maintenance of products. Due to improper installation

and improper use of the product, the product is damaged beyond the scope of this warranty. During the warranty period, We will choose to repair, replace (spare parts)

with new products. Labor charges or material costs will be appropriately collected over the warranty period.



• Products Application Cases

The date listed in this file is for reference only, and the specific date should be subject to the specific products, if any change, sorry for no notice .