

PRODUCT SPECIFICATION

Product Name: LED Down Light

Product model: NSDL-30-65K-SF NSDL-30-40K-SF NSDL-30-30K-SF

DESCRIPTION: LED Down Light (COB)

RoHS IECEE AC 110-240V Up to 30000hours

Features

- 1. Using die-casting aluminum with good appearance for high class looking.
- 2. Built-in constant current driver for high efficiency and stability.
- 3. Adopt imported COB as light source with high light efficiency and long lifespan.
- 4. Quick response time, the LED response time is nanosecond.
- 5. Environmental protection, no heavy metals and harmful gas.
- 6. Energy-saving, can save energy more 80% than traditional lights.
- 7. No flicker, start quickly, soft light, protect your eyes.
- 8. Easy to install and use.

Technical Parameter

Model	30W
LED model	COB 6042
LED Qty	1 PCS
Power	30W
Voltage	AC110-240 V

Working Frequency 50/60HZ

Power Efficiency ≥ 83%

Luminous Flux 2200LM

Efficiency $73 \text{LM/W} \pm 10\%$

Power Factor ≥ 0.5

Colour Temperature WH: 6500K(6020-7040)

NW: 4000K(3710-4260)

WW: 3000K(2875-3215)

CRI Ra≥80

Bean Angle 120º


Working $-20 \text{ to } + 50 \, ^{\circ}\text{C}$

Temperature


Service life 30,000hr life 5yr warranty

Relative Spectral Energy Distribution


NSDL-30-65K-SF



NSDL-30-40K-SF




NSDL-30-30K-SF





• Optical characteristic curve

NSDL-30




光通输出:2101 1m






Dimensions



- Instruction of wiring
- 1. Diagram of power supply wiring:

Installation Instructions



- 1. Fix the fixture with screw on ceiling;
- 2. Connect power and lamp;
- 3. Fix the lamp with fixture on ceiling by screw;
- 4. Finish installation and put the power on.

• Product Package

Packed in color box,20 PCS/ case

• Product Photos



• Packing size & Pictures:

Model	L (mm)	W (mm)	H (mm)
NSDL-30-65K-SF	230	45	230
NSDL-30-40K-SF	230	45	230
NSDL-30-30K-SF	230	45	230

内盒/230x45x230mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-30-65K-SF-V1

编码: 01.02.13.071.4589



内盒/230x45x230mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-30-40K-SF

第四: 01.02.13.071.4637

NASCO GLOBAL

NASCO GLOBAL

STATE OF THE STAT

内盒/230x45x230mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-30-30K-SF

第四: 01.02.13.071.4636

NASCO GLOBAL

NASCO GLOBAL

Long Ins 25.600 Hours

S YEARS

Removed Short

Removed Sho

01.02.13.041.3075 外箱/475x240x480mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-30-65K-SF

NASCO GLOBAL أساسكو المصالحة LED DOWN LIGHT		NASCO GLOBAL LED DOWN LIGHT	
المحدود المحاليات المحدود المحاليات المحدود المحاليات المحدود	SYEARS Warrany Cloud Studentson death of the control of the control death of the contr	NASCO GLOBAL معلون بور المعلون المعلو	SYEARS Warranty Lord J. 100001.300 Lord J. 100001 Lord J. 1

01.02.13.041.3408 外箱/475x240x480mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-30-40K-SF

NASCO GLOBAL أسالحو المعالية LED DOWN LIGHT		NASCO GLOBAL المسالحة LED DOWN LIGHT	
NASCO GLOBAL المعالمة المعالمعالمة المعالمة المعالمة المعالمة المعالمة المعالمة المعالمة الم	5 YEARS Warranty Chipman St. Monocharter Application Accidence Ap	Life with Light 30W LED DOWN LIGHT	SYEARS Warranty Carlo And Carlo Action Action Action Action Actio
SUVV LED DOWN LIGHT	سخے فی العمری	JUYY LED DOWN LIGHT	صنع في الصدين

01.02.13.041.3407 外箱/475x240x480mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-30-30K-SF

NASCO GLOBAL نسانخو المعالية LED DOWN LIGHT		NASCO GLOBAL أساكو الصالية LED DOWN LIGHT	
المالية الموحد الرام الموحد المالية الموحد المالية الموحد 192 () 192 () 193	5 YEARS Warranty Club 5 Warranty Club 6 Warranty David Station 1 Actineses John 1000 New Year John 1000	Life with Lisht الديد و بور الديد المحدد و المحدد	5 YEARS Warranty Club 2 Autority Comment John Storm 1 Autority Comment John Power John Power John Power John Power John Power John Comment John Comm
30W LED DOWN LIGHT	MADE IN CHINA مسلم في الصين	30W LED DOWN LIGHT	MADE IN CHINA مستع على الصنون

• Attentions

- 1. Make sure the power is off before maintenance.
- 2. Clean the glass of diffuser of lamp regularly to maintain good light transmittance.
- 3. Clean the dust of the shell to maintain good heat dissipation performance.
- 4. Be careful not to use water or corrosive solution for cleaning, it is better to use a dry cloth.

Warranty and After-sales Service

The period of guarantee is 5 years. Quality assurance is based on the correct storage, installation, use and maintenance of products. Due to improper installation

and improper use of the product, the product is damaged beyond the scope of this warranty. During the warranty period, We will choose to repair, replace (spare parts)

with new products. Labor charges or material costs will be appropriately collected over the warranty period.

Products Application Cases





The date listed in this file is for reference only, and the specific date should be subject to the specific products, if any change, sorry for no notice.