

#### PRODUCT SPECIFICATION

Product Name: LED Down Light

Product model: NSDL-40-65K-SF NSDL-40-40K-SF

NSDL-40-30K-SF

DESCRIPTION: LED Down Light (COB)

RoHS IECEE AC 110-240V Up to 30000hours

### Features

- 1. Using die-casting aluminum with good appearance for high class looking.
- 2. Built-in constant current driver for high efficiency and stability.
- 3. Adopt imported COB as light source with high light efficiency and long lifespan.
- 4. Quick response time, the LED response time is nanosecond.
- 5. Environmental protection, no heavy metals and harmful gas.
- 6. Energy-saving, can save energy more 80% than traditional lights.
- 7. No flicker, start quickly, soft light, protect your eyes.
- 8. Easy to install and use.
- Technical Parameter

Model	40W
LED model	COB 7660
LED Qty	1 PCS
Power	40W

Voltage AC110-240 V

Working 50/60HZ

Frequency

Power Efficiency ≥ 83%

Luminous Flux 3600LM

Efficiency 90LM/W  $\pm 10\%$ 

Power Factor  $\geq 0.9$ 

Colour Temperature WH: 6500K(6020-7040)

NW: 4000K(3710-4260)

WW: 3000K(2875-3215)

CRI Ra ≥ 80

Bean Angle 120º


Working  $-20 \text{ to} + 50 \,^{\circ}\text{C}$ 

Temperature


Service life 30,000hr life 5yr warranty

### Relative Spectral Energy Distribution


### NSDL-40-65K-SF



### NSDL-40-40K-SF




### NSDL-40-30K-SF




## Optical characteristic curve


### NSDL-40




光通输出:3458 lm



注:曲线为灯具在不同投射距离下的照射区域及区域内平均照度.




### Dimensions



- Instruction of wiring
- 1. Diagram of power supply wiring:

### Installation Instructions



- 1. Fix the fixture with screw on ceiling;
- 2. Connect power and lamp;
- 3. Fix the lamp with fixture on ceiling by screw;
- 4. Finish installation and put the power on.

## • Product Package

# Packed in color box,20 PCS/ case

# ● Product Photo



# • Packing size & Pictures:

<u> </u>			
Model	L (mm)	W (mm)	H (mm)
NSDL-40-65K-SF	305	55	305
NSDL-40-40K-SF	305	55	305
NSDL-40-30K-SF	305	55	305

## 内盒/305x55x305mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-40-65K-SF-V1



内盒/305x55x305mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-40-40K-SF-V1 01.02.13.071.4592



内盒/305x55x305mm/300g灰底白+A5(120g芯) E坑/四色/覆光膜/ NSDL-40-30K-SF-V1



01.02.13.041.3213 外箱/590x320x630mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-40-65K-SF V1

NASCO GLOBAL نساسکو العماليد LED DOWN LIGHT		NASCO GLOBAL نصابخو المصالية LED DOWN LIGHT	
NASCO GLOBAL المحاليات ال	SYEARS WATCHTS  JAMPIA, MORELAND  JAMPIA, MORELA	NASCO GLOBAL المحلف المحالف ا	SYEARS Warranty  Louis J. Models, No. Model-stated and the state of th

### 01.02.13.041.3215 外箱/590x320x630mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-40-40K-SF V1

NASCO GLOBAL المسالحة LED DOWN LIGHT		NASCO GLOBAL نساسکو الحسائید LED DOWN LIGHT	
NASCO GLOBAL المحالية المحالي	SYEARS Warranty  Color A MINIST NO WILL-BARGER  GAR VISION AND WILL-BARGER  GAR VISION AND WILL-BARGER  GAR VISION AND  GAR VISION  GAR VISION	PASCO GLOBAL لا المحالف المحا	SYEARS Warranty Closine 5 closin  Jour A. MODEL NO. MINEL-REPERFER JOHN MATCHES HERE  LONG MATCHES HERE JOHN MATCHES HERE JOHN MATCHES HERE  LONG MATCHES HERE JOHN MATCHES HERE JOHN MATCHES HERE LONG MATCHES HERE JOHN MATCHES HERE LONG MATCHES HERE JOHN MATCHES JOHN MATCHES HERE JOHN MATCHES HERE JOHN MATCHES JOHN

### 01.02.13.041.3214

### 外箱/590x320x630mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NSDL-40-30K-SF V1

NASCO GLOBAL انسانگو العباليد LED DOWN LIGHT		NASCO GLOBAL أساسكو المسائية LED DOWN LIGHT	
الرقر المرمد الرقاطية المحالية المحالي	SYEARS WATERTY  JAMES AND STREET	NASCO GLOBAL المحالف	SYEARS Warranty  Louis A, Model to D.  South

### • Attentions

- 1. Make sure the power is off before maintenance.
- 2. Clean the glass of diffuser of lamp regularly to maintain good light transmittance.
- 3. Clean the dust of the shell to maintain good heat dissipation performance.
- 4. Be careful not to use water or corrosive solution for cleaning, it is better to use a dry cloth.
- Warranty and After-sales Service

The period of guarantee is 5 years. Quality assurance is based on the correct storage, installation, use and maintenance of products. Due to improper installation

and improper use of the product, the product is damaged beyond the scope of this warranty. During the warranty period, We will choose to repair, replace (spare parts)

with new products. Labor charges or material costs will be appropriately collected over the warranty period.

### Products Application Cases





The date listed in this file is for reference only, and the specific date should be subject to the specific products, if any change, sorry for no notice.