

PRODUCT SPECIFICATION

Product Name: LED Panel Light

Product model: NS-20-R-65K NS-20-R-40K NS-20-R-30K

DESCRIPTION: LED Panel Light

RoHS IECEE AC 110-240V Up to 30000hours

Features

- 1. Using die-casting aluminum with good appearance for high class looking.
- 2. Built-in constant current driver for high efficiency and stability.
- 3. Imported SMD chip light source is adopted, with high light efficiency and long life.
- 4. Quick response time, the LED response time is nanosecond.
- 5. Environmental protection, no heavy metals and harmful gas.
- 6. Energy-saving, can save energy more 80% than traditional lights.
- 7. No flicker, start quickly, soft light, protect your eyes.
- 8. Easy to install and use.

Technical Parameter

Model	NS-20-R	
LED model	2835	
LED Qty	120 PCS	
Power	20W	
Voltage	AC110-240 V	

Working Frequency 50/60HZ

Power Efficiency ≥ 80%

Luminous Flux 1600LM

Efficiency $80 LM/W \pm 10\%$

Power Factor ≥ 0.9

Colour Temperature WH: 6500K(6020-7040)

NW: 4000K(3710-4260)

WW: 3000K(2875-3215)

CRI Ra ≥ 80

Bean Angle 120º


Working $-20 \text{ to} + 50 \,^{\circ}\text{C}$

Temperature


Service life 30,000hr life 5yr warranty

Relative Spectral Energy Distribution


NS-20-R-65K



NS-20-R-40K





NS-20-R-30K




• Optical characteristic curve


NS-20-R









Dimensions




- Model Diameter (mm) A(mm) B(mm) C(mm)
 NS-20-R / 225±1 200±1 19±1
- Instruction of wiring
- 1. Diagram of power supply wiring:



• Installation Instructions









- 1. Make a hole of the right size in the ceiling;
- 2. Connect power and lamp;
- 3. Attach the spring-loaded lamp to the ceiling;
- 4. Finish installation and put the power on.

Product Package

Packed in color box,20 PCS/ case

Product Photo





Packing size & Pictures:

Model	L (mm)	W (mm)	H (mm)
NS-20-R-65K	245	235	40
NS-20-R-40K	245	235	40
NS-20-R-30K	245	235	40

编码: 01.02.13.071.4581 内盒/245x235x40mm/ 250g灰底白+A2(100g芯) E坑/四色/覆光膜/NS-20-R-65K-V1



编码: 01.02.13.071.4661 内盒/245x235x40mm/ 250g灰底白+A2(100g芯) E坑/四色/覆光膜/NS-20-R-40K



编码: 01.02.13.071.4660 内盒/245x235x40mm/ 250g灰底白+A2(100g芯) E坑/四色/覆光膜/NS-20-R-30K



01.02.13.041.3029 外箱/505x215x490mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NS-20-R-65K

NASCO ورومها المسالح LED panel Light		NASCO GLOBAL LED panel Light	
NASCO GLOBAL	5 YEARS Warranty and 5 and 6	NASCO GLOBAL THE PROPERTY OF	5 YEARS Warranty Guido 5 could be decided to the d
	1,000 1,000 2,00		1.0F 1000128 200 1000128 1
20W LED panel light	د (2016015) 2222 MADE IN CHINA ضنع في الحين	20W LED panel light	و الاوران (See See See See See See See See See S
			說話 Windows 報題 母寶 以應證 Windows,

编码: 01.02.13.041.3420 外箱/505x215x490mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NS-20-R-40K

NASCO ولعظمار LED panel Light		NASCO GLOBAL LED panel Light	
NASCO GLOBAL	5 YEARS Warranty Claim 5 decide	NASCO GLOBAL	5 YEARS Warranty Club 2 or do b
	1807.1 1907.2 1908.2 1907.2 1		### 1950/1957 ARMS] ### 1950/1957 ARMS] ### 1950/1957 ARMS] ### 1950/1957 ARMS] #### 1950/1957 ARMS] #### 1950/1957 ARMS] #### 1950/1957 ARMS] #### 1950/1957 ARMS] ##### 1950/1957 ARMS] ####################################
20W LED panel light	المحاودة ال	20W LED panel light	a Carosserassee MADE IN CHINA صناح في الصنون
			激活 Windows 转割"设置"以激活 Windows。

编码: 01.02.13.041.3419 外箱/505x215x490mm/250g灰底白+535A(双120g芯) EB坑/四色/覆光膜/NS-20-R-30K

NASCO GLOBAL LED panel Light		به المحادث ال	
NASCO GLOBAL مرافقة عن مور	5 YEARS Warranty Classification of the Ministry Classification of the Ministry Company of the Ministry	NASCO GLOBAL Solver Like with Luter	5 YEARS Warranty Chapton 50 Was BR. Sala YOLKES W. CHESSES GAR OF THE SALE CONTROL
	1900 1900		COLUMN ASSESS
20W LED panel light	المودانيونيانيون MADE IN CHINA مستح في العسون	20W LED panel light	MADE IN CHINA مستح على العسون
			激活 Windows 转形设置"处题活 Windows。

Attentions

- 1. Make sure the power is off before maintenance.
- 2. Clean the glass of diffuser of lamp regularly to maintain good light transmittance.
- 3. Clean the dust of the shell to maintain good heat dissipation performance.
- 4. Be careful not to use water or corrosive solution for cleaning, it is better to use a dry cloth.
- Warranty and After-sales Service

The period of guarantee is 5 years. Quality assurance is based on the correct storage, installation, use and maintenance of products. Due to improper installation

and improper use of the product, the product is damaged beyond the scope of this warranty. During the warranty period, We will choose to repair, replace (spare parts)

with new products. Labor charges or material costs will be appropriately collected over the warranty period.

Products Application Cases



The date listed in this file is for reference only, and the specific date should be subject to the specific products, if any change, sorry for no notice.