



10A Switches Product's Data Sheet

Catalogue Number	NS5501,NS5502,NS5503,NS5504, NS5505,NS5506,NS5508, NS5515	
Product Name	One gang one way switch; One gang two way switch; Two gang one way switch; Two gang two way switch; Three gang one way switch; Three gang two way switch; Four gang one way switch; One gang bell switch;	
Range Name	Royal Series	
Standard Number	IEC 60669-1:2017	
SASO Number "Where Applicable"	NS5501	
Rated Voltage	250V~	
Rated Current	10AX	
Frequency	50/60Hz	
Product Dimensions	Height in mm	86mm
	Width in mm	90mm
	Depth in mm	34mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply	Red copper
	Terminals	Iron
Weight in gms		
Operating Cycles	≥40000 times	
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet	1
	Others	
Recommended Wire Size in mm	1.5~2.5mm ²	
Packaging Details (Number of Pcs in a Carton)	100	
Applied Test	H.V. Test	2000V
	Insulation	>5MΩ
	Temperature Rise	< 45 K

Product Front Image



Product Back Image





Switches & Sockets Product's Data Sheet



Catalogue Number	NS5563	
Product Name	One gang switched socket with USB	
Range Name	Royal Series	
Standard Number	BS 1363.2; SASO 2206; IEC 60950.1	
SASO Number "Where Applicable"	NS5563	
Rated Voltage	250V~	
Rated Current	13AX	
Frequency	50/60Hz	
Product Dimensions	Height in mm	86mm
	Width in mm	90mm
	Depth in mm	39mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply contact	Brass H65
	Terminals	Iron
Weight in gms		
Operating Cycles	≥30000 times	
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet in Qty	1
	Others	
Recommended Wire Size in mm	4mm ²	
Packaging Details (Number of Pcs in a Carton)	100	
Applied Test	H.V. Test	2000V
	Insulation Resistance	>5MΩ
	Temperature Rise	< 52 K

Product Front Image





Switches & Sockets Product's Data Sheet

Catalogue Number	NS5558, NS5559	
Product Name	13A socket, DP switch socket	
Range Name	Royal Series	
Standard Number	BS 1363.2 SASO 2203	
SASO Number "Where Applicable"	NS5558, NS5559	
Rated Voltage	250V~	
Rated Current	13AX	
Frequency	50/60Hz	
Product Dimensions	Height in mm	86mm
	Width in mm	90mm
	Depth in mm	31mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply contact	Brass H65
	Terminals	Iron
Weight in gms		
Operating Cycles	≥30000 times	
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet in Qty	1
	Others	
Recommended Wire Size in mm	4mm ²	
Packaging Details (Number of Pcs in a Carton)	100	
Applied Test	H.V. Test	2000V
	Insulation Resistance	>5MΩ
	Temperature Rise	< 52 K
Product Front Image		
		
Product Back Image		
		



Switches & Sockets Product's Data Sheet

Catalogue Number		NS5520
Product Name		20A switch
Range Name		Royal Series
Standard Number		IEC 60669-1:2017
SASO Number "Where Applicable"		NS5520
Rated Voltage		250V~
Rated Current		20AX
Frequency		50/60Hz
Product Dimensions	Height in mm	86mm
	Width in mm	90mm
	Depth in mm	38mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply contact	Red copper
	Terminals	Iron
Weight in gms		
Operating Cycles		≥10000 times
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet in Qty	1
	Others	
Recommended Wire Size in mm		4~6mm ²
Packaging Details (Number of Pcs in a Carton)		100
Applied Test	H.V. Test	2000V
	Insulation Resistance	>5MΩ
	Temperature Rise	< 45 K

Product Front Image



Product Back Image





Switches & Sockets Product's Data Sheet

Catalogue Number	NS5521	
Product Name	45A switch	
Range Name	Royal Series	
Standard Number	IEC 60669-1:2017	
SASO Number "Where Applicable"	NS5521	
Rated Voltage	250V~	
Rated Current	45AX	
Frequency	50/60Hz	
Product Dimensions	Height in mm	86mm
	Width in mm	90mm
	Depth in mm	35mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply contact	Red copper
	Terminals	Iron
Weight in gms		
Operating Cycles	≥10000 times	
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet in Qty	1
	Others	
Recommended Wire Size in mm	6~10mm ²	
Packaging Details (Number of Pcs in a Carton)	100	
Applied Test	H.V. Test	2000V
	Insulation Resistance	>5MΩ
	Temperature Rise	< 45 K

Product Front Image



Product Back Image





Switches & Sockets Product's Data Sheet

Catalogue Number	NS5561	
Product Name	Two gang DP switch socket	
Range Name	Royal Series	
Standard Number	BS 1363.2 SASO 2203	
SASO Number "Where Applicable"	NS5561	
Rated Voltage	250V~	
Rated Current	13AX	
Frequency	50/60Hz	
Product Dimensions	Height in mm	149mm
	Width in mm	90mm
	Depth in mm	30.5mm
Materials	Backplate	PC
	Clip-on Plate	PC
	Housing	PC
	Contacts Buttons	PC
	Moving Contact	Red copper+silver
	Load / Supply contact	Brass H65
	Terminals	Iron
Weight in gms		
Operating Cycles	≥30000 times	
Supplementary Accessories	Screw Caps in Qty	2
	Fixing Screws in Qty	2
	Paint Guard in Qty	-
	Installation leaflet in Qty	1
	Others	
Recommended Wire Size in mm	4mm ²	
Packaging Details (Number of Pcs in a Carton)	60	
Applied Test	H.V. Test	2000V
	Insulation Resistance	>5MΩ
	Temperature Rise	< 52 K

Product Front Image



Product Back Image

